

CK-Series PRICE COMPUTING SCALES



CK-P30Plus



CK-30Plus

- 1/6000 Resolution, Legal For Trade Approval #04055
- Stainless steel platter and ABS plastic sub-platter
- Ultra quick-response weight display
- Portable design: easily used in any location
- Tough high quality UV-sealed keypad
- Compact medium-sized footprint design
- Capacities: 30 x 0.005 lb, 60 x 0.01 lb
- Pole display models: CK-P30Plus & CK-P60Plus
- User-friendly PLU programming
- Quick operation keypad for high throughput
- Function keys: 4 or 34 PLUs, Save, Tare, and Zero
- External AC adapter with long power cord



Distributed by:



Commercial Food Processing & Packaging Equipment

www.mpbs.com

CK-Series PRICE COMPUTING SCALES

- Standard display models: CK-30Plus & CK-60Plus
- Pole display models: CK-P30Plus & CK-P60Plus
- High Resolution, NTEP Approved class III
- Large LCD displays with 6 digit pricing and weight
- AC adapter included
- Non-Pole models: 4 direct PLU keys programmable with tare and unit price!
- Pole models: 34 direct PLU keys programmable with tare and unit price!
- Built-in rechargeable battery: over 100 hours of continuous use!



	CK-30Plus	CK-P30Plus	CK-60Plus	CK-P60Plus
Shipping Weight.....	13 lb.	16 lb.	13 lb.	16 lb.
Capacities and Graduations.....	30 x 0.005 lb.	30 x 0.005 lb.	60 x 0.01 lb.	60 x 0.01 lb.
Maximum Tare.....	30 lb.	30 lb.	60 lb.	60 lb.
Direct PLU Keys (Tare & Unit Price).....	4	34	4	34
Product Dimensions (Height).....	125 mm / 4.5 "	575 mm / 22.6 "	125 mm / 4.5 "	575 mm / 22.6 "
Product Dimensions (Length).....	340 mm / 13.4 "	340 mm / 13.4 "	340 mm / 13.4 "	340 mm / 13.4 "
Product Dimensions (Width).....	320 mm / 12.6 "	320 mm / 12.6 "	320 mm / 12.6 "	320 mm / 12.6 "
Liquid Crystal Displays (LCD).....	Weight / Unit Price / Total Price: 6 Digits, 999.999 Max			
Platter Size Width.....	300 mm / 11.8 "			
Platter Size Length.....	225 mm / 8.9 "			
Accreditation.....	NTEP Class III, OIML, CE, ISO 9002, UL			
Internal Power Supply, (AC Cord)	120 Volts AC @ 60 Hz, AC Power Cord			
External Adapter.....	120 Volts AC @ 60 Hz to 9VDC @ 800mA			
Battery Specifications.....	100 hrs with Backlight Off or 48 hrs with Backlight On (Continuous use)			
Power Consumption & Fuse Rating	Approximately 10 Watts / Fuse: 250 Volts, 1.5 Amp, 20mm			

Distributed by:



2820 East Washington Blvd
Los Angeles CA 90023
Tel: 323-268-8514, 800-421-6265
www.mpbs.com
contact@mpbs.com