

# SAFETY DATA SHEET

## 1. Identification

<b>GHS product identifier</b>	<b>STEEL-IT #1002 Polyurethane (spray/brush grade)</b>
<b>Product code</b>	1002
<b>Version #</b>	01
<b>Issue date</b>	02-01-2012
<b>CAS #</b>	Mixture
<b>Recommended use</b>	Not available.
<b>Recommended Restrictions</b>	Not available.
<b>Manufacturer information</b>	Stainless Steel Coatings, Inc 835 Sterling Road South Lancaster, MA, 01561 Contact person: CHEMTREC sds@steel-it.com (978) 365-9828
<b>SDS number</b>	SDS-1002

## 2. Hazards identification

### GHS classification

<b>Physical hazards</b>	Flammable liquids	Category 3
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure	Category 2 (Kidney, Lung)
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2

### GHS label elements



**Hazard statement** Flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause respiratory irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs (Kidney, Lung) through prolonged or repeated exposure.

### Precautionary statement

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Avoid breathing gas/mist/vapors/spray. Avoid release to the environment.

**Response** IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a doctor if you feel unwell. Collect spillage.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

**Specific hazards** Overexposure to mists/vapors of this product may cause headache, dizziness, nausea, and respiratory tract irritation.

### 3. Composition/information on ingredients

Components	CAS #	Percent
Stoddard solvent	8052-41-3	20 - 30
4-Chloro-.alpha.,.alpha.,.alpha.-trifluorotoluene	98-56-6	20 - 25
Solvent naphtha (petroleum), medium aliph.	64742-88-7	5-7
Chromium	7440-47-3	2 - 5
Distillates, (petroleum), Hydrotreated Light	64742-47-8	2 - 5
Nickel	7440-02-0	2 - 3
Xylene	1330-20-7	1 - 2
Ethylbenzene	100-41-4	<0.1
Quartz	14808-60-7	<0.1

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First aid measures

#### First aid procedures

**Inhalation** If symptomatic, move to fresh air. Get medical attention if symptoms persist.  
**Skin** Wash area with soap and water. Get medical attention if irritation develops or persists.  
**Eye** Check for and remove any contact lenses. Immediately flush with plenty of water for up to 15 minutes. Get medical attention immediately.  
**Ingestion** Get medical attention if any discomfort occurs.

**Most important symptoms and effects, both acute and delayed** Prolonged or repeated contact may dry skin and cause irritation. Sensitization. Skin irritation. Upper respiratory tract irritation. Headaches, dizziness and nausea.

**Notes to physician** Treat symptomatically.

### 5. Fire-fighting measures

**Suitable extinguishing media** Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical. Water fog.  
**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.  
**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed.  
**Protective equipment and precautions for firefighters** Move container from fire area if it can be done without risk.

### 6. Accidental release measures

**Personal precautions** Ensure adequate ventilation. Wear suitable protective clothing. See Section 8 of the MSDS for Personal Protective Equipment.  
**Environmental precautions** Prevent entry into waterways, sewer, basements or confined areas.  
**Methods for containment** Eliminate all ignition sources. Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements or confined areas.  
**Methods for cleaning up** Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  
Small Liquid Spills: Absorb up with sand or other non-combustible absorbent material.  
Never return spills in original containers for re-use. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination.

### 7. Handling and storage

**Handling** Use only with adequate ventilation. Wash thoroughly after handling. Observe good industrial hygiene practices. Avoid inhalation of vapors and contact with skin and eyes.  
**Storage** Store locked up. Keep container tightly closed and in a well-ventilated place. Store in closed original container at room temperature. Store away from incompatible materials.

## 8. Exposure controls / personal protection

### Control parameters

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Chromium (7440-47-3)	TWA	0.5 mg/m <sup>3</sup>	
Ethylbenzene (100-41-4)	TWA	20 ppm	
Nickel (7440-02-0)	TWA	1.5 mg/m <sup>3</sup>	Inhalable fraction.
Quartz (14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.
Solvent naphtha (petroleum), medium aliph. (64742-88-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Stoddard solvent (8052-41-3)	TWA	100 ppm	
Xylene (1330-20-7)	STEL TWA	150 ppm 100 ppm	

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Engineering controls** Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

### Personal protective equipment

**Eye/face protection** Use approved safety goggles or face shield.

**Skin protection** Wear appropriate chemical resistant clothing to prevent any possibility of skin contact. Nitrile chemical resistant gloves are recommended.

**Respiratory protection** In case of inadequate ventilation, use respiratory protection. In case of inadequate ventilation or when the product is heated, use suitable respiratory equipment with gas filter for organic gas.

**Hand protection** Wear appropriate chemical resistant gloves. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.

## 9. Physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Physical state</b>	Liquid.
<b>Color</b>	Silver.
<b>Form</b>	Liquid.
<b>Odor</b>	Characteristic of solvents.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/Freezing point</b>	Not available.
<b>Boiling point</b>	278.6 - 397.4 °F (137 - 203 °C)
<b>Flash point</b>	98.6 °F (37 °C)
<b>Evaporation rate</b>	0.9 (butyl acetate = 1)
<b>Flammability (solid, gas)</b>	Not available.
<b>Flammability limits in air, lower, % by volume</b>	0.9 %
<b>Flammability limits in air, upper, % by volume</b>	10.5 %
<b>Vapor pressure</b>	5.3 mmHg at 20 °C
<b>Vapor density</b>	6.2 (Air = 1)
<b>Relative density</b>	1.15
<b>Solubility (H<sub>2</sub>O)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	< 1 (Log Pow)
<b>Auto-ignition temperature</b>	932 °F (500 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	700 cP (Brookfield #4 spindle @100rpm)
<b>VOC (Weight %)</b>	490 g/l
<b>Bulk density</b>	Not Applicable.

## 10. Stability and reactivity

<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Will not occur.
<b>Conditions to avoid</b>	Heat, sparks, flames. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Metal oxides.

## 11. Toxicological information

### Toxicological data

Components	Test Results
Xylene (1330-20-7)	Acute Oral LD50 Rat: 4300 mg/kg
<b>Routes of exposure</b>	Inhalation. Skin contact.
<b>Toxicological information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Acute toxicity</b>	Overexposure to mists/vapors of this product may cause headache, dizziness, nausea, and respiratory tract irritation. Causes skin, eye and respiratory tract irritation.
<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	May cause eye irritation on direct contact.
<b>Respiratory sensitization</b>	None known.
<b>Skin sensitization</b>	May cause an allergic skin reaction.
<b>Mutagenicity</b>	There is no data to indicate that any component present at greater than 0.1% may present a risk.
<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>ACGIH Carcinogens</b>	
Chromium (CAS 7440-47-3)	A4 Not classifiable as a human carcinogen.
Ethylbenzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Nickel (CAS 7440-02-0)	A5 Not suspected as a human carcinogen.
Quartz (CAS 14808-60-7)	A2 Suspected human carcinogen.
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	A4 Not classifiable as a human carcinogen.
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	3 Not classifiable as to carcinogenicity to humans.
Stoddard solvent (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to the following organs through prolonged or repeated exposure: Respiratory system.
<b>Teratogenicity</b>	There is no data to indicate that any component present at greater than 0.1% may present a risk.
<b>Symptoms</b>	Prolonged or repeated contact may dry skin and cause irritation. Sensitization. Skin irritation. Upper respiratory tract irritation. Headaches, dizziness and nausea.

## 12. Ecological information

### Ecotoxicological data

Components	Test Results
Xylene (1330-20-7)	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss): 8 mg/l 96 Hours
<b>Ecotoxicity</b>	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Persistence / degradability</b>	No data available.
<b>Bioaccumulation</b>	No data available.

**Mobility** No data available.  
**Other adverse effects** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 13. Disposal considerations

**Disposal methods** Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container.

**Waste from residues / unused products** Dispose of waste and residues in accordance with local authority requirements.

**Contaminated packaging** Since emptied containers retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

#### ADR

**UN number** UN1263  
**UN proper shipping name** PAINT (Stoddard solvent)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packing group** III  
**Environmental hazards** Yes  
**Tunnel restriction code** D/E  
**Labels required** 3  
**Special precautions for user** Not available.

#### IATA

**UN number** UN1263  
**UN proper shipping name** Paint (Stoddard solvent)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packing group** III  
**Environmental hazards** Yes  
**ERG Code** 3L  
**Special precautions for user** Not available.

#### IMDG

**UN number** UN1263  
**UN proper shipping name** PAINT (Stoddard solvent)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packing group** III  
**Marine pollutant** Yes  
**EmS No.** F-E, S-E  
**Special precautions for user** Not available.

#### RID

**UN number** UN1263  
**UN proper shipping name** PAINT (Stoddard solvent)  
**Transport hazard class(es)** 3  
**Subsidiary class(es)** -  
**Packing group** III  
**Environmental hazards** Yes  
**Labels required** 3  
**Special precautions for user** Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** No information available.

### 15. Regulatory information

**Regulatory information** The product is classified and labelled in accordance with EC directives or respective national laws.

#### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other information

**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently available.

**Revision date** 02-01-2012